



GE Profile™ 30" Built-In Twin Flex Convection Wall Oven Model# PT9200SLSS



FEATURES

Fuel Type	Electric
Oven Interior	2 Halogen Interior Oven Lights (Lower) 2 Halogen Interior Oven Lights (Upper)
Oven Features	6-Pass Broil Dual (Upper) 8-Pass Bake Element (Both Ovens) 8-Pass Broil Dual (Lower)
Configuration	Double Oven
Product Type	Single/Double Oven
Oven Rack Features	2 Self-Clean Heavy Duty Flat Oven Racks, 1 Self-Clean Roller Rack 2 Upper / 3 Lower Embossed Rack Positions
Cooking Technology	Traditional Upper; Convection Lower
Self-Clean Oven Door Lock	Automatic
Control Type	Glass Touch
Cooking System	True European Convection with Precise Air (Lower)
Oven Cooking Modes	Convection Bake Multi/Single Rack Convection Roast Pizza Slow Cook Thermal Bake Thermal Broil
Oven Cleaning Type	Self-Clean (Both Ovens)
Oven Control Features	Audible Preheat Signal Auto Recipe Conversion (Lower) Certified Sabbath Mode (Lower) Control Lock Capability Cook Time C° or F° Programmable Delay Bake Option Delay Clean Option Dual Broil Electronic Clock & Kitchen Timer Light Self Clean Mode (Lower) Mis-Wire Detection Oven Light Pad Proof Mode (Lower) Temperature Probe (Lower) Warm Mode (Both Ovens)

- Fit Guarantee - Replacing a similar wall oven from GE Appliances or another brand? GE wall ovens are guaranteed for an exact fit or GE Appliances will pay up to \$300 toward modifications. [See offer criteria and details](#)
- True European Convection with Precise Air (lower oven) - Enjoy golden brown, perfectly even results with a third heating element and a reversing fan that provides enhanced heat and air circulation
- 5.0 cu. ft. total oven capacity (2.8 lower; 2.2 upper) - Cook sides or desserts in the upper oven while roasting a 22-lb. turkey in the lower oven
- Flexible and versatile cooking options - Prepare two different foods at two different temperatures at the exact same time
- Rapid Preheat - The upper oven preheats twice as fast as standard GE models, so everyday meals are ready in less time
- Self-clean, heavy-duty roller rack - Easily access everything from a heavy roast to a delicate dessert thanks to durable racks that glide smoothly on ball bearings and stand up to the heat of self-clean
- Slow cook - Create fall-off-the-bone short ribs while you're at work
- Pizza mode - Get a perfectly crisp pizza crust without burning your toppings
- Self-clean oven - Cleans the oven cavity without the need for scrubbing
- Glass touch controls - Set temperatures easily and quickly wipe away fingerprints with this smooth control pad.

Have more questions? Please contact 1-800-626-2000



GE Profile™ 30" Built-In Twin Flex Convection Wall Oven

Model# PT9200SLSS

APPROXIMATE DIMENSIONS(HxDxW)

- 28 1/8 H x 29 3/4 W x 26 3/4 D

CAPACITY

- Total Capacity (cubic feet) - 5.0cu ft
- Capacity (Cu. Ft.) - 2.2 Upper / 2.8 Lower

APPEARANCE

- Handle Color - Stainless Steel
- Frameless Oven Door(s) - Stainless
- Installation - Built-In
 - Side-by-Side
 - Under Cabinet
 - Under Cooktop
 - Undercounter
- Oven Door Features -
- Color Appearance - Stainless Steel
- Handle Design - Sculptured

WEIGHTS & DIMENSIONS

- Overall Depth (in) - 26 3/4in
- Cabinet Width (in) - 30in
- Oven Interior Dimensions (lower) (null) - 24 x 12 1/2 x 16
- Overall Width (in) - 29 3/4in
- Oven Interior Dimensions (upper) (null) - 24 x 8 3/4 x 17 7/8
- Net Weight (lb) - 190lb
- Approximate Shipping Weight (lb) - 212lb
- Overall Height (in) - 28 1/8in
- Cutout Dimensions (w x h x d) (in.) (null) - 28-1/2 x 27-1/4 x 23-1/2

POWER / RATINGS

- Bake Wattage - 1700W Upper / 2200W Lower
- Amp Rating at 208V - 20
- Broiler Wattage - 2750W Upper / 2950W Lower
- Convection Wattage - 1300W
- KW Rating at 240V - 3.9
- Amp Rating at 240V - 20
- KW Rating at 208V - 2.9

WARRANTY

- Labor Warranty - Limited 1-year entire appliance
- Parts Warranty - Limited 1-year entire appliance
- Warranty Notes - See written warranty for full details

CERTIFICATIONS

- Claims & Certifications - ADA Compliant
 - Star-K
 - UL
 - California Prop 65

Have more questions? Please contact 1-800-626-2000